



**SPEC SHEET : GLAND PACKING**  
**SERIES : KN5305/PTFE+ARAMID FIBER CORNER**

**Material :**

made of PTFE yarns and the reinforced Aramid corner of Aramid fiber. This structure, Enhances the lubricant of Aramid and reinforces the strength of the pure PTFE packing.

It is made of synthetic composite, Aramid corner and reinforces the strength. finished braiding packing. Aidmer76-020A was special processed This special combination packing uses in the sealing of high pressure piston pump. It can used in piston pumps, valves, pulp, paper, waste water treatment, petrochemical, and other industrial applications.

**Application :** Suitable for oils, solvents, diluted acids and alkalies. abrasive media like sand, slurry, sewage, brine etc.

**Not suitable for :** Concentrated acids and lyes, alkalimetals, fluorine and fluorine compounds at high temperatures, oxygen.

**Application Data:**

	Rotary	Reciprocating	Valve
Pressure:bar	27.6	300	300
Speed:m/s	18	3	1.5
pH Range	2 - 12		
Temp. °C	-17 to +260		



**K.N.PROGRESS CO.,LTD.**

333/11 The Canary Private Village., Moo.4  
 Srinakarin Rd., T.Bang Mueang, A.Mueang Samutprakan,  
 Samutprakan 10270

Tel : 0815529616, 095-969-6649